

2000 ORDERING SUPPLEMENT MIDDLE EAST

SAVANA CARGO

Osmidcgg

REQUIRED ON ALL MIDDLE EAST ORDERS		
RPO	DESCRIPTION	
EXP	Processing Option: GMODC, Export	X
K53	Fuel Sender Assy., Robust Fuel System	X
NM2	Leaded Fuel Provisions	X
R6K	Processing Option: Middle East	X
T62	Daytime Running Lights Delete	X
UC2	Speedometer: Kilo/Miles, Kilo Odometer, Positive Bias	X
UD4	Speed Warning Device	X
V60	Vehicle Statement - Incomplete Vehicle Required with YF7	X
V87	Vehicle Certification Label Not Available with YF7	X
VC5	Shipping Label	X
VK3	Front License Plate Bracket	X
VPH	Export Vehicle Preparation - Includes (BAG) Export Parts pkg., (VR6)Tie Down Hook, (V70)Tow Hook	X
Z5X	Mirror: Outside, Rearview, Arabic Language Warning, Requires DE2/DE5 Mirrors	X

**NOTES: MUST ORDER WINDOW PACKAGE, ZW2, ZW3, ZW4 OR ZW6.
MUST ORDER UL2 OR UL5.**

MODEL AND POWERTRAIN AVAILABILITY					
MODEL	DESCRIPTION	ENG.	DISPL.	TRANS.	
TG11405	Cargo Van (C5Y) GVW 7100 lbs	L31	5.7L V8	M30	
TG21405	Cargo Van (C6P) GVW 8600 lbs	L31	5.7L V8	MT1	
TG21705	Cargo Van (C6P) GVW 8600 lbs	L31	5.7L V8	MT1	
TG31705	Cargo Van, 155" Wheelbase (E23) GVW 9500 lbs	L65	6.5I V8	MT1	

R

OTHER AVAILABLE EXPORT OPTIONS		
DH6	Mirrors: Inside, Front Vanity, LH/RH, Sunshade, Illuminated	A
NP5	Leather Wrapped Steering Wheel	A
UL0	Radio: AM/FM Stereo, Seek/Scan, Cassette, Clock, ETR - Requires UL2	A
UL2	European Radio Frequency - Requires UL0 and ZQ2; Includes U75	A
UL5	Radio Delete	A
YF2	Sales Package Ambulance Upfitter: Includes (B31) Covering Floor Vinyl, Front, Full Width, (G80) Axle Positraction Limited Slip, (ZW3) Window Package Rear Door, Side Rear Door.	A
YF7	Upfitter Package: Includes (A19) Windows: Side Door Swing-Out, (BG5) Floor Covering Delete, (C60) Front Air Conditioning, (DE5) Mirrors: Outside, Rearview, LH/RH, Remote Control, Electric, Heated, Folding, (KW2) Generator 124 AMP, (PNC) Panel Trim: Front Doors, Side Rear Door, Rear Doors, (V22) Chrome Grille, (V37) Chrome Front/Rear Bumpers, (YB9) Interior Paint Delete, (ZP0) Temporary Driver Seat, (ZQ2) Power Windows, Power Door Locks, (ZQ3) Cruise Control and Tilt Steering Column In Addition TG11405 Requires ZW3 and N90/P06 Or Requires ZW6, N90 and YK6 TG21405/TG21705 Requires P06 and ZW3	A
YK6	Processing Option, SEO. Requires 6L2 Or Requires ZW6 & N90	A
6L2	Headliner: Full Length. Not Available TR9, YF7. Requires YK6	A

R

R

R

R

R

R

R

R

R

R

EXPORT RESTRICTIONS:	
AJ1	Deep Tinted Glass - Not Available
KL5	Alternative Fuel Compatible Engine - Not Available
Z82	Trailer, Special Equipment - Not Available

2000 LIGHT DUTY TRUCKS DOMESTIC

SAVANA CARGO

SAVANA CARGO

2 WHEEL DRIVE	G11405
2 WHEEL DRIVE	G21405
2 WHEEL DRIVE	G21705
2 WHEEL DRIVE	G31405
2 WHEEL DRIVE	G31705

"STEP by STEP"

STEP #1:	SELECT	MODEL CODE Review Standard Equipment
STEP #2:	SELECT	PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE
STEP #3:	SELECT	POWER TEAM REQUIREMENTS
STEP #4:	SELECT	ADDITIONAL OPTIONS
STEP #5:	SELECT	COLOUR, TRIM AND PAINT APPLICATION CODE

STEP #1: SELECT MODEL CODE – Review Standard Equipment

SAFETY/SECURITY		ZW9
Air bags: Driver and Passenger		S
Brakes: Four wheel antilock system. Power, self adjusting.		S
Child Safety Door Locks: On rear and side loading doors		S
Daytime Running Lights		S
Passlock™ Security System		S
Side Guard Door Beams: Front doors and side cargo door		S
Single Two-Sided Key		S
EXTERIOR		
Bumpers: Front and rear; painted argent. Rear bumper with entry assist step.		S
Corrosion Protection: Two-sided galvanized steel, except roof; 7-stage phosphate bath for entire vehicle; anti-chip coating on lower body area		S
Doors: Left hand and right hand front side doors; swing-out, hinged, side cargo doors		S
Rear load doors, full opening; hidden hinges; bumper extends beyond opened doors		S
Glass: All windows Solar-Ray™ tinted		S
Grille: Moulded plastic grille; integral "GMC" letters at centre		S
Headlamps, Halogen: Single rectangular, sealed beam; hi/low beam		S
Horns, Dual		S
Lights: Backup Lamps; Combination Parking/Direction/Hazard; Combination Tail/Stop/Direction/Hazard; Headlamps; License Plate Lamp; Side Marker Lamps with Reflectors; Centre High Mounted Stop Lamp.		S
Mirrors: Left hand and right hand manual control, black, fold-away		S
Spare Tire Carrier: Winch-type; under body at rear, behind axle		S
Wheels: Steel wheel, argent with black center cap.		S
Windshield Wipers and Washers: Intermittent wiper system, wet-arm washer system		S
INTERIOR		
Armrests: Left hand and right hand side doors; padded		S
Assist Handle: Front passenger side		S
Cup Holders: Two, in instrument panel		S
Floor Covering: Embossed black vinyl, front and rear, full width		S
Headliner: Cloth above driver and passenger seats		S
Headlamps On Warning Alarm		S
Heater and Defogger: Outside air heater with windshield and side window defoggers		S
Instruments: Gauges - Speedometer, Odometer, Fuel, Voltmeter, Temperature, Oil Pressure and Trip Odometer		S
Lighter, Cigarette		S
Lights: Front, centre and rear dome lamps with front door-actuated switches		S
Parcel Tray: On top surface of instrument panel extension (with L29 or L65 only)		S
Power Outlet, Auxiliary: one covered auxiliary power outlet on instrument panel		S
Radio Equipment: Electronically Tuned AM/FM Stereo Radio with Seek-Scan and Digital Clock		S
Seats: Reclining high back front bucket driver and passenger seats, with integral head restraints and map pockets		S
Steering Wheel and Column: Black energy-absorbing steering column, black vinyl wheel		S
Stowage Box: In instrument panel extension, lighted		S
Sunshades: Colour-keyed; right hand sunshade has full map strap		S
Tools: Scissor-type jack and wheel wrench. Located at right rear of vehicle		S

S Standard

2000 LIGHT DUTY TRUCKS

SAVANA CARGO

STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE

REFER TO GENERAL INFORMATION SECTION FOR HOW TO ORDER INFORMATION WHEN CHANGING POWERTRAIN

NOTE: SEE POWER TEAM CHARTS FOR CORRECT UPGRADES COMPATIBILITY

OPTION DESCRIPTION	OPTION CODE	SELECT-A-UNIT CODES	
		1	2
PREFERRED EQUIPMENT GROUP	--	1SA	1SB
BODY CODE: Standard	ZW9	X	X
Engine: Vortec 4300 SFI V6 (G11405, G21405, G21705)	L35	U	U
Engine: Vortec 5700 SFI V8 (G31405, G31705)	L31	U	U
Transmission: 4 Speed Automatic w/Overdrive (G11405)	M30	X	X
Transmission: 4 Speed Automatic w/Overdrive (G21405, G21705)	M30	U	U
Transmission: 4 Speed Automatic W/Overdrive (G31405, G31705)	MT1	X	X
GVWR: 2767 kgs (6100 lbs) (G11405)	C5M	U	U
GVWR: 3311 kgs (7300 lbs) (G21405, G21705)	C6A	U	U
GVWR: 4309 kgs (9500 lbs) (G31405, G31705)	E23	X	X
Axle, Rear: 3.42 Ratio (G11405, G21405, G21705)	GU6	U	U
Axle, Rear: 3.73 Ratio (G31405, G31705)	GT4	U	U
Tires: P215/75R-15/N ALS SBR Blackwall (G11405)	YCU	U	U
Tires: LT225/75R-16/D ALS SBR Blackwall (G21405, G21705)	YHP	U	U
Tires: LT245/75R-16/E ALS SBR Blackwall (G31405, G31705)	YHH	X	X
Seats: High Back Buckets, Driver and Passenger	ZX2	U	U
Air Conditioning: Front	C60		U
Convenience Group: Tilt Wheel and Speed Control	ZQ3		X

X Option Included In Select-A-Unit DO NOT DELETE

U Option Included In Select-A-Unit and May Be Deleted if Substitute Option is Specified

2000 LIGHT DUTY TRUCKS**STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE**

Description	Model Code	Body Code	Select-A-Unit Code	Option Code
-------------	---------------	--------------	-----------------------	----------------

2 WHEEL DRIVE – 1500 SERIES**STANDARD – 135 INCH WHEELBASE**

Model Price.....G11405.....ZW9.....1.....1SA
 Preferred Equipment Group Price.....G11405.....ZW9.....2.....1SB

2 WHEEL DRIVE – 2500 SERIES**STANDARD – 135 INCH WHEELBASE**

Model Price.....G21405.....ZW9.....1.....1SA
 Preferred Equipment Group Price.....G21405.....ZW9.....2.....1SB

STANDARD – 155 INCH WHEELBASE

Model Price.....G21705.....ZW9.....1.....1SA
 Preferred Equipment Group Price.....G21705.....ZW9.....2.....1SB

2 WHEEL DRIVE – 3500 SERIES**STANDARD – 135 INCH WHEELBASE**

Model Price.....G31405.....ZW9.....1.....1SA
 Preferred Equipment Group Price.....G31405.....ZW9.....2.....1SB

STANDARD – 155 INCH WHEELBASE

Model Price.....G31705.....ZW9.....1.....1SA
 Preferred Equipment Group Price.....G31705.....ZW9.....2.....1SB

2000 LIGHT DUTY TRUCKS

SAVANA CARGO

STEP #3: SELECT POWER TEAM REQUIREMENTS

Engine, Transmission, Axle Ratio and GVWR Code Must Be Specified

G11405

					GVWR Code	§ C5M	¶ C5Y
					kgs	2767	3220
					lbs	6100	7100
					Axle Ratio	3.42	3.42 3.73
Engine Type	Displacement	Fuel System	Net HP	Transmission Type	Axle Ratio Codes		
L35 V6	4.3 Litre	SFI	200 @ 4400	M30-Automatic w/Overdrive	GU6	GU6	GT4
L30 V8	5.0 Litre	SFI	220 @ 4600	M30-Automatic w/Overdrive	GU6	GU6	---
L31 V8	5.7 Litre	SFI	245 @ 4600	M30-Automatic w/Overdrive	---	GU6	---

§ Requires YCU Tires

¶ Requires YHA, YHB or YHM Tires

G21405, G21705

					GVWR Code	§ C6A	¶ C6P
					kgs	3311	3901
					lbs	7300	8600
					Axle Ratio	3.42	3.73 4.10
Engine Type	Displacement	Fuel System	Net HP	Transmission Type	Axle Ratio Codes		
L35 V6	4.3 Litre	SFI	200 @ 4400	M30-Automatic w/Overdrive	GU6	---	---
				MT1-Automatic w/Overdrive	---	---	GT5
L30 V8	5.0 Litre	SFI	220 @ 4600	M30-Automatic w/Overdrive	GU6	---	---
L31 V8	5.7 Litre	SFI	245 @ 4600	M30-Automatic w/Overdrive	GU6	---	---
				MT1-Automatic w/Overdrive	---	* GT4	* GT5
L65 V8	6.5 Litre 395 Cu. In.	Turbo Diesel	195 @ 3400	MT1-Automatic w/Overdrive	---	#GT4	GT5

§ Requires YHP Tires

¶ Requires YHF Tires

* Horsepower is 250 @ 4600 RPM

Not Available model G21405.

G31405, G31705

					GVWR Code	E23	
					kgs	4309	
					lbs	9500	
					Axle Ratio	3.42	3.73 4.10
Engine Type	Displacement	Fuel System	Net HP	Transmission Type	Axle Ratio		
L31 V8	5.7 Litre	SFI	250 @ 4600	MT1-Automatic w/Overdrive	---	GT4	GT5
L29 V8	7.4 Litre	SFI	290 @ 4000	MT1-Automatic w/Overdrive	* GU6	GT4	GT5
L65 V8	6.5 Litre 395 Cu. In.	Turbo Diesel	195 @ 3400	MT1-Automatic w/Overdrive	---	#GT4	GT5

* Not Available with G80

Not Available model G31405.

STEP #4: SELECT ADDITIONAL OPTIONS

Description

Option Code

ENGINES: – Refer to Power Teams Chart for compatibility.

Vortec 4300 Sequential Fuel Injection (SFI) V6.

With MT1 includes extra capacity engine oil cooling L35

Vortec 5000 Sequential Fuel Injection (SFI) V8 L30

Vortec 5700 Sequential Fuel Injection (SFI) V8.

With MT1 includes an auxiliary transmission oil cooler and extra capacity engine oil cooling.

Optional with: G11405, G21405, G21705.....L31

.....G31405, G31705.....L31

Vortec 7400 Sequential Fuel Injection (SFI) V8.

Includes extra capacity engine oil cooling and an auxiliary transmission oil cooler L29

6.5 Litre (395 Cu. In.) Turbo Diesel V8.

Includes an auxiliary engine oil cooler and an auxiliary transmission oil cooler. Includes KW2, dual batteries – one is on frame rail behind driver's door, the other is in right hand corner under hood.

Optional with: G21405, G21705.....L65

.....G31405, G31705.....L65

Alternative Fuel Compatible Engine:

Provides only the engine with internal modifications for operation with natural or propane gas.

Requires L31 and MT1. Requires C6P with G21405, G21705. Not Available G11405. KL5**TRANSMISSION: – Refer to Power Teams Chart for compatibility**

4-Speed Electronic Automatic with Overdrive M30

4-Speed Electronic Automatic with Overdrive MT1

GVWR: – Refer to Power Teams Chart for compatibility**G11405**

2767 kgs (6100 lbs) C5M

3220 kgs (7100 lbs) C5Y

G21405, G21705

3311 kgs (7300 lbs) C6A

3901 kgs (8600 lbs) Includes KW2. C6P

G31405, G31705

4309 kgs (9500 lbs) Includes KW2. Includes an auxiliary transmission oil cooler. E23

AXLES, REAR: – Refer to Power Teams Chart for compatibility

Ratio Codes 3.42.....GU6

.....3.73.....GT4

.....4.10.....GT5

Locking Differential. **Not Available** with GU6 on G31405 or G31705.....G80**TIRES:**

P215/75R-15/N All Season Steel Belted Radial Blackwall. Front, Rear and Spare.

Requires C5M. Optional with: G11405.....YCU

P235/75R-15/X All Season Steel Belted Radial Blackwall. Front, Rear and Spare.

Requires C5Y. Optional with: G11405.....YHA

P235/75R-15/X All Season Steel Belted Radial White Stripe. Front, Rear and Spare.

Requires C5Y and YF7. Optional with: G11405.....YHB

P235/75R-15/XL All Season Steel Belted Radial White Outline Lettered. Front, Rear and Spare.

Requires C5Y and YF7. Optional with: G11405.....YHM

LT225/75R-16/D All Season Steel Belted Radial Blackwall. Front, Rear and Spare.

Requires C6A. Optional with: G21405, G21705.....YHP

LT225/75R-16/E All Season Steel Belted Radial Blackwall. Front, Rear and Spare.

Requires C6P. Optional with: G21405, G21705.....YHF

LT245/75R-16/E All Season Steel Belted Radial Blackwall. Front, Rear and Spare.

Optional with: G31405, G31705.....YHH

Spare Tire Delete. Deletes Spare Tire, Wheel and Jack.

Optional with: with YCU on G11405.....ZX9

.....with YHA on G11405.....ZX9

.....with YHP on G21405, G21705.....ZX9

.....with YHF on G21405, G21705.....ZX9

.....with YHH on G31405, G31705.....ZX9

2000 LIGHT DUTY TRUCKS

SAVANA CARGO

STEP #4: SELECT ADDITIONAL OPTIONS

	Description	Option Code
	SEATS AND SEAT TRIM:	
	High Back Buckets, Driver and Passenger. With 'G' Trim includes inboard armrests and Scotchgard™.	
	Optional with: 'W' or 'G' Trim.....	ZX2
	High Back Bucket, Driver side only. Deletes standard passenger side airbag.	
	Passenger seat cannot be added later. With 'G' Trim includes inboard armrests and Scotchgard™.	
	Optional with: 'W' or 'G' Trim.....	ZX1
	AIR BAG, DRIVER SIDE ONLY:	
	Deletes the passenger side Air Bag.	
	Requires ZX2. Requires C6P on G21405 and G21705.	
	Not Available on G11405.	AJ3
	AIR CONDITIONING:	
	Front. Includes instrument panel integrated outside air system and increased capacity cooling.	
	Recommended for front seat area cooling only. Included with C69. Required with YF2.	
	Optional with: SAU 1.....	C60
	Front and Rear. Includes C60, KW2, C36 and rear overhead mounted recirculating air system.	
R	Not Available YF2 or YF7.	
	Optional with: SAU 1 on G11405, G21405, G21705.....	C69
	 SAU 2 on G11405, G21405, G21705.....	C69
	 SAU 1 on G31405, G31705.....	C69
	 SAU 2 on G31405, G31705.....	C69
	ALTERNATOR, 124 AMP:	
	Included with C69, C6P, L65. Included with G31405, G31705.	
	Optional with: G11405, G21405, G21705.....	KW2
	AMBULANCE PREP PROVISIONS:	
	Includes B31, G80, ZW3, dual 100 AMP alternators, front and rear chrome bumper and provisions for rear air conditioning and rear heater.	
	Requires L65, MT1, GT5. Requires C60 with SAU 1.	
	Not Available C36, C69, DE5, TR9, YA2.	
	Deletes dome lamp and rear cargo lamp, headliner and TR9 with SAU 2.	
	Optional with: with ZR7 and SAU 1 on G31705.....	YF2
	 without ZR7 and SAU 1 on G31705.....	YF2
	 SAU 2 on G31705.....	YF2
	APPEARANCE, DELUXE:	
	Includes chrome grille and chrome front and rear bumpers.	
R	Optional with: SAU 1 or 2.....	ZR7
	COLD CLIMATE PROVISION:	
	Includes engine block heater. Not Available L65.....	V10
	CONVENIENCE GROUPS:	
	Power Windows and Power Door Locks	ZQ2
	Tilt Wheel and Speed Control	SAU 1..... ZQ3
	DOOR:	
	Sliding side rear door. Includes Child Safety Door Lock.	
	Swing out side door is standard. Not Available YF2.....	YA2
	FLOOR COVERING DELETE:	
	Black vinyl, front floor seating area only, full width.	
	Deletes the standard rear black vinyl floor covering.....	B31
	HEATER:	
	Rear. Located on left side, ahead of rear wheelhouse.	
R	Included with C69. Not Available YF2 or YF7	C36
	LIGHTING, AUXILIARY:	
	Includes reading lamps, front and side door stepwell lamps, underhood lamp.	
	Not Available YF2 or YF7.....	TR9

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code	
MIRRORS, EXTERIOR:		
Left hand and right hand electric remote control, with defog feature; folding. Requires C60 or C69. Requires ZQ2. Not Available YF2. Not Available B3D	DE5	
PAINT SCHEME: See Colour, Trim and Seat Availability Chart. Solid		ZY1
RADIO EQUIPMENT:		
Antenna, Power. Not Available with UL5	U75	
Radio Delete. Deletes Antenna	UL5	
Electronically Tuned AM/FM Stereo Radio with Seek-Scan, Stereo Cassette Tape and Digital Clock. Includes fixed mast antenna, premium dual front and rear speakers	UM6	
SCHOOL BUS CHASSIS EQUIPMENT:		
Deletes right hand front rubber mat and right hand front floor insulation. Requires ZX1. Requires L31 or L65. Not Available with Z82. Not Available with DE5. Includes visual and audible brake warning system, and Incomplete Vehicle Document. Optional with:	G31405, G31705 B3D	
TRAILERING, SPECIAL EQUIPMENT:		
Heavy Duty. Includes Weight Distributing Platform Type Trailer Hitch and 8-lead type wiring harness with heavy duty flasher. Additional cooling not required. Not Available with B3D.....	Z82	
R UPFITTER PACKAGE, RECREATIONAL VEHICLE:		
Includes (BG5) Floor Covering Delete, (C60) Air Conditioner, Front, (V22) Chrome Radiator Grille, (V37) Chrome Bumpers, Front/Rear, (YB9) Interior Paint Delete, (ZP0) Temporary Driver Seating Arrangement, (ZQ2) Convenience Package, Power Window/Door Locks, (ZQ3) Convenience Package, Cruise Control, Tilt Steering Wheel, (ZW3) Window Package; Rear, Side Rear Doors. Not available C36, C69 or TR9.	YF7	
WHEEL TRIM: Bright trim rings with chromed centre caps.....		P06
WINDOWS, SWING-OUT:		
Rear doors. Requires ZW2. Included with A19	A18	
Rear side cargo door. Includes A18. Requires ZW3, ZW4 or ZW6	A19	
WINDOW PACKAGES:		
Windows are stationary unless ordered with A18 or A19 (except with ZW6 which includes swing-out left hand centre body glass).		
Rear doors, fixed.....	ZW2	
Rear doors and rear side doors, fixed (sliding or swing out)	ZW3	
Rear doors, right hand side, fixed.....	ZW4	
Complete body (includes swing-out left hand centre body glass).....	ZW6	
DESCRIPTION	Order Code	Lead Time Days

SPECIAL EQUIPMENT WHEN INSTALLED AT ASSEMBLY PLANT**HEADLINER, FULL LENGTH:**

Not Available with TR9, YF2 or YF7

6L2

PAINTS: Solid. Requires 01U Colour Code One.

Green, Woodland	9V5	--
Tan, Doeskin	9V9	--
Yellow, Wheatland	9W3	--
Orange, Tangier	9W4	--

2000 LIGHT DUTY TRUCKS

SAVANA CARGO

STEP #5: SELECT COLOUR, TRIM AND PAINT APPLICATION CODE

ZY1 PAINT APPLICATION

Body Code	Seat Ordering Information			Interior Trim		
	Type	Seat Material	Option Code	Navy	Neutral	Medium Gray
ZW9	High Back Bucket	Vinyl	ZX2 §	26W	52W	92W
	High Back Bucket	Custom Cloth	ZX2 §	26G	52G	92G

Exterior Paint Colour	Code	Available Combinations		
Medium Storm Gray (Met)	14U	X	---	X
Fernmist Green (Met)	31U	---	X	X
Indigo Blue (Met)	39U	X	X	X
Black	41U	---	X	X
Summit White	50U	X	X	X
Dark Carmine Red (Met)	51U	---	X	X
Light Autumnwood (Met)	55U	---	X	---
Fire Red	74U	---	X	X
Dark Bronzemist (Met)	76U	---	X	X

§ Seat option may be changed, check SEATS AND SEAT TRIM.

DATE: February 14, 2000
REVISION NO: 00-3

**GENERAL MOTORS OVERSEAS DISTRIBUTION
CORPORATION**

**2000
UPDATE**

**GMC
SAVANA CARGO
TRUCK TECHNICAL PAGES**

Attached is revision 00-3 of the Light Duty Truck Technical Pages.

The information contained in the Technical Pages is confidential and should not be disclosed to unauthorized persons or used for non-business purposes.

MODEL SELECTION SUMMARY

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD/OPT)	STANDARD ENGINE/ TRANS	OPTIONAL ENGINE/ TRANS	GVWR KG (LB)	GAWR KG (LB) FRONT/ REAR	MAXIMUM PAYLOAD KG (LB)	MAX GROSS TRAILER WT/ TONGUE LOAD KG (LB)
SAVANA CARGO								
G10								
G10 REGULAR WHEELBASE	G11405/ ZW9	2/1	4300 V6/A4	— 5000 V8/A4	2767 (6100)	1437/1436 (3168/3167)	639 (1410)	2449/* (5400) 2631/* (5800)
G10 REGULAR WHEELBASE	G11405/ ZW9	2/1	4300 V6/A4	— 5000 V8/A4 5700 V8/A4	3220 (7100)	1633/1780 (3600/3968)	1078 (2379)	2449/* (5400) 2631/* (5800) 3311/* (7300)
G20								
G20 REGULAR WHEELBASE	G21405/ ZW9	2/1	4300 V6/A4	— 5000 V8/A4 5700 V8/A4	3311 (7300)	1624/1987 (3580/4380)	1102 (2431)	2222/* (4900) 2540/* (5600) 2767/* (6100)
G20 REGULAR WHEELBASE	G21405/ ZW9	2/1	4300 V6/A4	— 5700 V8/A4 6.5L V8/A4	3901 (8600)	1724/2431 (3800/5360)	1570 (3462)	2449/* (5400) 3765/* (8300) 4037/* (8900)
G20 EXTENDED WHEELBASE	G21705/ ZW9	2/1	4300 V6/A4	— 5000 V8/A4 5700 V8/A4	3311 (7300)	1624/1987 (3580/4380)	1018 (2245)	2222/* (4900) 2540/* (5600) 2767/* (6100)
G20 EXTENDED WHEELBASE	G21705/ ZW9	2/1	4300 V6/A4	— 5700 V8/A4 6.5L V8/A4	3901 (8600)	1860/2431 (4100/5360) 1950/2431 (4300/5360)	1485 (3275)	2449/* (5400) 3765/* (8300) 4037/* (8900)
G30								
G30 REGULAR WHEELBASE	G31405/ ZW9	2/1	5700 V8/A4	— 7400 V8/A4 6.5L V8/A4	4309 (9500)	1950/2760 (4300/6084)	1860 (4101)	3674/* (8100) 4536/* (10000) 3992/* (8800)
G30 EXTENDED WHEELBASE	G31705/ ZW9	2/1	5700 V8/A4	— 7400 V8/A4 6.5L V8/A4	4309 (9500)	1950/2760 (4300/6084)	1772 (3907)	3674/* (8100) 4536/* (10000) 3992/* (8800)

*Trailer tongue weight should be 10 to 15% of total loaded trailer weight. (up to 1000 lbs).

POWERTRAINS

ENGINES					
	VORTEC 4300 V6	VORTEC 5000 V8	VORTEC 5700 V8	VORTEC 7400 V8 HD	6.5L V8 DIESEL HD
Order Code	L35 (Standard G11405/ 21405/21705)	L30	L31	L29	L65
Availability	G11405, G21405 and G21705	G11405 and G21405/ G21705 w/C6A	All	G31405/ G31705	G21405/ G21705 w/C6P and G31405/ G31705
SAE Net Kilowatts @ rpm (Horsepower @ rpm)	149 @ 4400 (200 @ 4400)	164 @ 4600 (220 @ 4600)	190 @ 4600 (255 @ 4600)	216 @ 4000 (290 @ 4000)	145 @ 3400 (195 @ 3400)
SAE Net Torque N-m @ rpm (lb-ft @ rpm)	339 @ 2800 (250 @ 2800)	380 @ 2800 (280 @ 2800)	447 @ 2800 (330 @ 2800)	556 @ 3200 (410 @ 3200)	583 @ 1800 (430 @ 1800)
Fuel System	SFI	SFI	SFI	SFI	Indirect Fuel Injection
Standard Delco Freedom Battery (12 volt, negative ground) Cold Cranking Amps @ -17.8° C (0°F)	600	600	600	600	2 @ 600 each
Standard Delcotron Alternator Maximum Capacity Amps	100 ¹	100	100	124	124

¹124 amp alternator is required on or above 3901 kg (8600 lb) GVWR.²100 amp alternator is standard on G21405/G21705 w/C6P.

TRANSMISSIONS		
	ELECTRONIC AUTOMATIC 4-SPEED OVERDRIVE W/TORQUE CONVERTER CLUTCH (4L60-E) (Includes brake/transmission shift interlock)	ELECTRONICALLY CONTROLLED AUTOMATIC 4-SPEED W/OD HEAVY DUTY (4L80-E) (Includes brake/transmission shift interlock)
Order Code	M30 (Standard w/C5M, C5Y, C6A)	MT1 (Standard w/C6P, E23)
Application	L35/L30/L31	L35 HD/L31 HD/L29/L65
Gear Ratios		
First	3.06	2.48
Second	1.63	1.48
Third	1.00	1.00
Fourth	0.70	0.75
Reverse	2.29	2.08

REAR AXLES									
Availability	G11405 w/C5M	G11405 w/C5Y	G21405/G21705 w/C6A	G21405/G21705 w/C6P w/o L65	G21405/G21705 w/C6P and L65 only; G31405/G31705				
Make	GM	GM	GM	GM	GM				
Capacity (kg)	1588 (3500) Semi-Floating	1814 (4000) Semi-Floating	2177 (4800) Semi-Floating	2585 (5700) Full-Floating	2760 (6084) Full-Floating				
Pinion and Ring Gear Type	Hypoid	Hypoid	Hypoid	Hypoid	Hypoid				
Engine Availability ¹	L35/L30	L35 L30 L31	L35 L30 L31	L31 L35/ L31	L29 L29/ L31/ L65	L29/ L31/ L65			
Axle Ratio Code	GU6 (Standard)	GU6	GT4	GU6 (Standard)	GT4	GT5	GU6	GT4 ²	GT5
Ratio	3.42	3.42	3.73	3.42	3.73	4.10	3.42	3.73	4.10
Pinion Teeth	12	12	11	12	11	10	12	11	10
Ring Gear Teeth	41	41	41	41	41	41	41	41	41
Ring Gear Diameter mm (in.)	218 (8.6)	218 (8.6)	218 (8.6)	241 (9.5)	241 (9.5)	241 (9.5)	267 (10.5)	267 (10.5)	267 (10.5)

Note: Axle ratio availability depends on model, powertrain and emissions selected.

¹Engine applications are heavy duty (HD) at 3901 kg (8600 lb) GVWR or above.²Standard axle on G31405 and G31705.

BRAKES

Type	Power Self-Adjusting 4-Wheel Anti-Lock	Power Self-Adjusting 4-Wheel Anti-Lock	Power Self-Adjusting 4-Wheel Anti-Lock
Application	G11405; G21405 G21705 w/C6A	G21405/G21705 w/C6P and w/o L65	G21405/G21705 w/C6P and L65; G31405/G31705
Front Rotor Size mm (in.)	Disc 294 x 32 (11.57 x 1.25)	Disc 318 x 32 (12.5 x 1.26)	Disc 318 x 32 (12.5 x 1.26)
Rear Size mm (in.)	Drum 283 x 70 (11.15 x 2.75)	Drum 330 x 63.5 (13 x 2.5)	Drum 330 x 88.9 (13 x 3.5)
Booster Type	Vacuum	Hydraulic	Hydraulic
Parking Brake Type Operation	Cable to Rear Wheels Pedal	Cable to Rear Wheels Pedal	Cable to Rear Wheels Pedal

STANDARD CHASSIS FEATURES

AIR BAGS	Driver and passenger	SUSPENSION, FRONT	Independent
ENGINE BLOCK HEATER		Capacity G11405; G21405/ G21705 w/C6A G21405/G21705 w/C6P; G31405/ G31705	1633 kg (3600 lb)
EXHAUST SYSTEM	Aluminized stainless steel single exhaust with converter	Springs	1950 kg (4300 lb)
FRAME	Full-length, all-welded ladder-type construction	Capacity G11405; G21405/ G21705 w/C6A G21405 w/C6P G21705 w/C6P w/o L65 G21705 w/C6P and L65; G31405/ G31705	Coil
FUEL TANK	Forward of rear axle between frame rails	Shock Absorbers	816 kg (1800 lb) each 862 kg (1900 lb) each
GVWR	117 litres (25.8 imperial gal.)	Stabilizer Bar	930 kg (2050 lb) each
C5M-G11405	2767 kg (6100 lb)		975 kg (2150 lb) each
C6A-G21405/G21705	3311 kg (7300 lb)		32mm (1.26") piston diameter
E23-G31405/G31705	4309 kg (9500 lb)		30mm (1.18") diameter
STEERING	Integral Power	SUSPENSION, REAR	Multi-leaf
		Springs	
		Capacity G11405 w/C5M G11405 w/C5Y G21405/G21705 w/C6A G21405/G21705 w/C6P G31405/G31705	718 kg (1583 lb) each 900 kg (1984 lb) each 993 kg (2190 lb) each 1215 kg (2680 lb) each 1380 kg (3042 lb) each
		Shock Absorbers	32mm (1.26") diameter
		WHEELS	
		Type	Five disc, painted argent with 4 black plastic centre caps
		Size G11405 G21405/21705/ G31405/31705	381mm x 152mm (15" x 6") 406mm x 165mm (16" x 6.5")
		Attachment G11405 G21405/21705 with C6A G21405/21705 with C6P; G31405/31705	5 bolts on 127mm (5") circle 6 bolts on 139.7mm (5.5") circle 8 bolts on 165mm (6.5") circle

TIRES

KEY: ALS = ALL-SEASON SBR = STEEL-BELTED RADIAL PLY BW = BLACKWALL WS = WHITE STRIPE WOL = WHITE OUTLINE LETTERED

TIRE DESCRIPTION	FRONT, REAR, SPARE
P215/75R15/N	YCU (Standard w/G11405)
P235/75R15/X	YHA
P235/75R15/X	YHB
P235/75R15	YHM
LT225/75R16/D	YHP (Standard w/G21405/21705)
LT225/75R16/E	YHF
LT245/75R16/E	YHH (Standard w/G31405/31705)

DIMENSIONS

SERIES	G10	G20		G30	
MODEL	REGULAR WHEELBASE	REGULAR WHEELBASE	EXTENDED WHEELBASE	REGULAR WHEELBASE	EXTENDED WHEELBASE
MODEL NUMBER	G11405/ZW9	G21405/ZW9	G21705/ZW9	G31405/ZW9	G31705/ZW9
EXTERIOR DIMENSIONS					
BODY					
Wheelbase mm (in.)	3429 (135.0)	3429 (135.0)	3937 (155.0)	3429 (135.0)	3937 (155.0)
Overall Length mm (in.)	5555 (218.7)	5555 (218.7)	6063 (238.7)	5555 (218.7)	6063 (238.7)
Overall Height Nominal mm (in.)	C5M-2022 (79.6)	C6A-2096 (82.5)	C6A-2060 (81.1)	E23-2131 (83.9)	E23-2096 (82.5)
Maximum Width mm (in.)	2017 (79.4)	2012 (79.2)	2012 (79.2)	2017 (79.4)	2012 (79.2)
Bumper to Axle					
Front mm (in.)	859 (33.8)	859 (33.8)	859 (33.8)	859 (33.8)	859 (33.8)
Rear mm (in.)	1267 (49.9)	1267 (49.9)	1267 (49.9)	1267 (49.9)	1267 (49.9)
Ground to Top of Rear Load Floor mm (in.)	617 (24.3)	696 (27.4)	704 (27.7)	737 (29.0)	737 (29.0)
Ground Clearance Front/Rear mm (in.)	175(6.9)/170 (6.7)	206 (8.1)/183 (7.2)	206 (8.1)/203 (8.0)	221 (8.7)/216 (8.5)	221 (8.7)/216 (8.5)
Side Load Door Sliding (YA2)					
Opening Height mm (in.)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)
Opening Width mm (in.)	1036 (40.8)	1036 (40.8)	1036 (40.8)	1036 (40.8)	1036 (40.8)
Side Load Door Swing-Out (E24)					
Opening Height mm (in.)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)
Opening Width mm (in.) —Both Doors Open	1186 (46.7)	1186 (46.7)	1186 (46.7)	1186 (46.7)	1186 (46.7)
Rear Load Door					
Opening Height mm (in.)	1242 (48.9)	1242 (48.9)	1242 (48.9)	1242 (48.9)	1242 (48.9)
Opening Width mm (in.)	1445 (56.9)	1445 (56.9)	1445 (56.9)	1445 (56.9)	1445 (56.9)
Turning Diameter Curb-to-Curb m (ft)	13.7 (45.1)	13.8 (45.2)	16.3 (53.4)	14.5 (47.5)	16.3 (53.5)
SIGN PANEL AREA mm (in.)	2959 x 1440 (116.5 x 56.7)	2959 x 1440 (116.5 x 56.7)	3467 x 1440 (136.5 x 56.7)	2959 x 1440 (116.5 x 56.7)	3467 x 1440 (136.5 x 56.7)
STEP-UP HEIGHT mm (in.)					
Front Door	419 (16.5)	483 (19.0)	483 (19.0)	521 (20.5)	523 (20.6)
Second Door	394 (15.5)	457 (18.0)	457 (18.0)	495 (19.5)	498 (19.6)

DIMENSIONS (CONT'D)

SERIES	G10	G20		G30	
MODEL	REGULAR WHEELBASE	REGULAR WHEELBASE	EXTENDED WHEELBASE	REGULAR WHEELBASE	EXTENDED WHEELBASE
MODEL NUMBER	G11405/ZW9	G21405/ZW9	G21705/ZW9	G31405/ZW9	G31705/ZW9
INTERIOR DIMENSIONS					
Headroom Front mm (in.)	1031 (40.6)	1031 (40.6)	1031 (40.6)	1031 (40.6)	1031 (40.6)
Legroom Front mm (in.)	1044 (41.1)	1044 (41.1)	1044 (41.1)	1044 (41.1)	1044 (41.1)
Shoulder Room Front mm (in.)	1748 (68.8)	1748 (68.8)	1748 (68.8)	1748 (68.8)	1748 (68.8)
Hip Room Front mm (in.)	1621 (63.8)	1621 (63.8)	1621 (63.8)	1621 (63.8)	1621 (63.8)
Load Floor Length w/Front Seats mm (in.)	3233 (127.3)	3233 (127.3)	3741 (147.3)	3233 (127.3)	3741 (147.3)
Inside Width @ Beltline mm (in.)	1917 (75.5)	1917 (75.5)	1917 (75.5)	1917 (75.5)	1917 (75.5)
Inside Width between Wheelhousings w/mat mm (in.)	1336 (52.6)	1336 (52.6)	1334 (52.5)	1336 (52.6)	1334 (52.5)
Interior Height mm (in.)	1367 (53.8)	1367 (53.8)	1367 (53.8)	1367 (53.8)	1367 (53.8)
Cargo Volume w/Front Seat litres (cu ft)	7569 (267.3)	7569 (267.3)	8971 (316.8)	7569 (267.3)	8971 (316.8)